

Motor Oil 15w/40 Multifleet

Aegis 15w/40 Multifleet is a quality lubricant based on a blend of high viscosity mineral oils and selected additives giving total protection for motor vehicle engines. It is suitable for all makes and models including the latest multivalve, multi cam and turbocharged variants. Aegis 15w/40 motor oil is designed for European and Japanese vehicle use under all operating conditions. It is also recommended for use in light and medium diesel engines including turbocharged. This oil offers the highest protection against wear, rust, oxidation, piston scuffing, valve gear wear and engine deposits.

APPLICATIONS:

Meets and exceeds API Classification SM, SL, SJ/CG-4, CF

BENEFITS:

Meets above requirements for engine wear and deposit control.
Extra protection for stop and go traffic conditions.
Protection against viscosity and thermal breakdown.
Maintains viscosity over a range of temperatures and provides stay in grade performance through the recommended drive train.
The highest protection in both hot and cold sections of the engine, even in severe stop and go service.
Has excellent cold start and engine warm up properties.
Provides the highest protection against foam, rust, corrosion and oxidation.

Typical Properties	
SAE Grade	15w/40
Kinematic Viscosity @ 40°C, cSt	117.9
Kinematic Viscosity @ 100°C, cSt	14.2
Viscosity Index	136
Pour Point °C	-20
Flash Point °C	215