

Motor Oil Series III

AEGIS SERIES III/10, 20, 30, 40, 50 MOTOR OIL

Aegis Series III oils are a range of specialized mono-grade diesel engine oils for use where non multigrade engine oil performance is required.

APPLICATIONS:

Meets and exceeds API Classification CD/SF

Series III/10 – for use in some hydraulic systems mainly in earthmoving equipment.

Series III/20 – for use in some transmissions and gearboxes.

Series III/30 – for use in diesel engines where a monograde oil is recommended.

Series III/40 – for use in diesel engines where a monograde oil is recommended, as well as some gearboxes and transmissions.

Series III/50 – for use in fuller and Roadranger gearboxes and applications requiring a non EP SAE gear oil.

Where a Caterpillar TO-2 oil is required.

Where an Allison C3 oil is required.

Where MIL-L-45199B oils are required.

Where MIL-L-2104D oils are required.

In Mack Engines requiring Mack EO-J oils.

BENEFITS:

Superior protection from deposits in both hot and cold sections of the engine.

Maximum protection from rust, corrosion and foam.

Longer oil drain intervals in large diesel engines.

Longer engine life and low maintenance costs.

TYPICAL PROPERTIES	10	20	30	40	50
SAE Grade	10	20	30	40	50
Viscosity @ 40°C, cSt	40.0	56.2	111.5	149.0	197.0
Viscosity @ 100°C, cSt	6.37	7.88	12.16	14.7	17.2
Viscosity Index	108	105	98	96	95
Pour Point, °C	-27	-27	-21	-19	-11
Flash Point, °C	228	246	254	264	271