



Orders: 0800 655-645 Ph: 07 867-5321 Fax: 07 867-5004 Web: www.aegisoil.co.nz

Aegis Oil Product Specification Sheet

Aegis Hydraulic Oils



Aegis have a range of 5 High Performance mineral based Hydraulic Oils formulated to lubricate and protect hydraulic systems operating at high pressures and temperatures.

These oils are compatible with most metals used in hydraulic systems, including copper and bronze. The oils also offer excellent antifoam and rust protection, plus excellent demulsibility and filterability.

Aegis Hydraulic Oils are suitable for use where antiwear hydraulic oils are specified in systems using vane, piston or gear pumps, and are specially suited for use in hydraulic systems operating in arduous conditions such as fork lifts, front end loaders, diggers and earth moving power control systems, including those with axial piston pumps for which bronze corrosion protection is often of concern. Meets Sperry Vickers I-286-S and M-2950-S specifications. These oils are also entirely suitable for use as circulating oils.

ZINC

Aegis hydraulic oils contain Zinc as an anti wear additive, but where silver bearing surfaces are present, a special Non-Zinc hydraulic oil is available by request.

Typical Properties	ISO 32	ISO 46	ISO 68	ISO 100	ISO 150
Viscosity @ 40c cst	32.0	46.0	68.0	100.0	150.0
Viscosity @ 100c cst	5.5	6.9	8.8	11.3	14.7
Viscosity Index	106	104	102	98	97
Pour Point c	-20	-20	-20	-15	-12
Flash Point c	+210	+220	+235	+250	+260